

# STATIO


## PILLAR

TYPE 2 AC CHARGER



STATIONS

# #SmartCharging





STATIO

# DATA SHEET

## INPUT

Input Supply	Single Phase 230 V AC
Voltage Range	200 - 240V AC
Frequency Range	50Hz $\pm$ 3% (IS 12360)
Rated Current	< 32A
Power Factor	~0.95

## OUTPUT

No. of Outlets	Single
Vehicle Connector	IEC-62196 Type 2 AC
Output Power	7.68kW
Output Current	32 A configurable at 10A, 16A & 30A
Efficiency	~95%
Cable Length	5 meter or more

## PHYSICAL ATTRIBUTES

Place of installation	Indoor/Outdoor
Installation Type	Floor Mounting
IP Protection degree	IP 55
Operating Ambient Temperature	-30°C to +50°C
Cooling	Forced air ventilated
Indications	Backlit LED for charging states



# DATA SHEET

## PROTECTION AND SAFETY COMPLIANCES

Protection

Short Circuit Protection

Over-Voltage and Under-Voltage protection

Ground fault detection

Internal Residual Current Detection

Over temperature protection (Derating/Shutdown)

## TROUBLESHOOTING

Diagnostic Function

Over the air automatic software updates

Charger to CMS

OCPP v1.6 or later

## COMMUNICATION

Network interface


Ethernet, Wi-Fi, 3G, 4G









User Authentication

RFID, Mobile App




# FEATURES




-  Wi-Fi enabled for a seamless charging experience
-  Smart connectivity through the Statiq app
-  Set charging prices according to the demand
-  Real-time charging and data monitoring
-  Integrated payment systems for a hassle free experience
-  Start and stop from anywhere, at anytime
-  Over the air updates and troubleshooting
-  Auto-cut off upon charging completion

## Discover



## Pay



## Charge

